

# Fireflex Tank™

Open Top Water Reservoir for  
Wildland/Urban Interface  
Firefighting



## Features

- Self-supporting; no frame or parts to assemble
- Compact for easy storage
- Lightweight
- Rugged industrial fabric which is mold and mildew resistant
- Highly visible contrasting tank colors
- Unique floatation collar design; no inflation required
- Extra large diameter open top for easy helicopter bucket filling
- Models/sizes available to suit all helicopter buckets
- Low maintenance; easy to clean and repair
- Multi-point tie down system for protection from rotor wash
- Easy discharge through standard 3" NPT outlets
- Quick and easy set up by 1 to 2 people, depending on size

## Ground Application

In ground operations, fire-fighters can use the Fireflex Tank as an emergency water reservoir, or as a readily available water source during prescribed burning.

The self-supporting Fireflex Tank may be easily filled from the nearest water source creating a portable water reservoir. In remote areas, the Fireflex Tank can be filled by pumping water from a natural source such as a stream or lake.



## Aerial Application

When access to water supply is otherwise limited pilots who are heli-bucketing can quickly fill their buckets from a Fireflex Tank and proceed to the fire site. The Fireflex Tank can be replenished with water while the pilot ferries between the water source and the fire site, thereby maximizing valuable helicopter time.

## Other Applications

- Potable water reservoir for camps (with optional potable water fabric)
  - Water relay tank
  - Long or short term water storage
  - Protecting urban interface exposures
- Please note: If using exclusively for mixing foams and/or retardants use Fireflex Hazmat Tanks.

## Accessories and Options

- Ball valves/fittings
- Ground pads
- Transport bags
- Repair kits
- Secondary internal impact pads available for large size tanks

Drainage Outlets:

- 1" to 6" NPT

Specifications on overleaf.



Fireflex Division of SEI Industries Ltd. 7400 Wilson Avenue, Delta, British Columbia, Canada V4G 1E5  
Tel: (604) 946-3131 Fax: (604) 940-9566 E-mail: seisales@sei-ind.com Web site: www.sei-ind.com

# Fireflex Tank™ Specifications

Fireflex Tanks Capacities		100 Imp. 120 US 455 L	250 Imp. 300 US 1140 L	500 Imp. 600 US 2275 L	1000 Imp. 1200 US 4546 L	1500 Imp. 1800 US 4800 L	2500 Imp. 3000 US 11365 L	4000 Imp. 4800 US 18200 L	5000 Imp. 6000 US 22700 L	8000 Imp. 10000 US 36320 L	12000 Imp. 14400 US 54500 L
Part No.		112	253	506	1012	1518	2530	4048	5060	80100	120144
Collapsed Dimension	Inches	10x18x28	12x20x30	15x24x33	15x24x38	15x24x40	20x29x40	20x29x48	22x30x48	32x32x54	38x24x62
	cm	25x46x71	30x50x76	38x61x84	38x61x96	38x61x101	51x73x101	51x73x122	56x76x122	81x81x137	95x61x158
Weight	Pounds	13	22	38	55	69	92	106	123	200	250
	kg	6	10	17	25	31	42	48	56	91	113
Filled Outside Diameter	Inches	60	84	84	124	133	164	195	209	236	260
	Metres	1.5	2.1	2.1	3.15	3.4	4.2	5	5.3	6	6.6
Collar Inside Diameter	Inches	30	52	54	60	84	108	131	144	144	168
	Metres	.75	1.3	1.4	1.5	2.1	2.7	3.3	3.7	3.7	3.7
Height (Filled)	Inches	23	32	38	40	48	48	60	60	80	93
	Metres	.6	.8	.97	1	1.2	1.2	1.5	1.5	2	2.4
Outlets	#	1	2	2	2	2	2	4	4	4	4
Size	Inches	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT

Other sizes available (custom) on request.  
Specifications subject to change without notice.

**Distributed by:**

**TYPE**  **ONE**

Type One Incident Support LLC  
 PO Box 8209, Bend, OR 97708-8209  
 T: 541-330-4340 F: 541-330-4341  
 E-Mail: support@typeoneproducts.com  
 Website: www.typeoneproducts.com