



# Low-Profile Tank

## Open Top Water Tank for Structural Firefighting

Fully self-supporting with an open top design and a low collar for easy filling, the Fireflex Low-Profile (LP) Tank is perfect for structural firefighting in rural areas.

LP Tanks enable rural fire departments to use isolated water supplies and still obtain sufficient water for effective firefighting.

Lighter and safer than traditional framed tanks, the LP Tank can be easily deployed and quickly filled from a water tender in just minutes.



**The Low-Profile tank can be easily filled by a water tender**

## Features

- Frameless, no parts to assemble and can be easily deployed by one person
- Low weight, high strength fabric will last after many deployments
- The solid flotation collar will rise automatically when filling eliminating the need for inflation
- Multi-point tie down system for firm grounding during operations
- Extra large top opening and low collar allow for fast and easy filling from water tenders
- Includes a lifting strap inside the center of the tank for easy cleaning and drying

## Accessories

- 2 ea. 1" to 6" NPT drainage outlets
- Ground pads
- Transport bags
- Ball valves/special fittings
- Repair kits
- Hose Caddy tripod stand to support filler hoses

Distributed by:



Type One Incident Support LLC  
PO Box 8209, Bend, OR 97708-8209  
T: 541-330-4340 F: 541-330-4341  
E-Mail: support@typeoneproducts.com  
Website: www.typeoneproducts.com

**FireFlex Division of SEI Industries Ltd. 7400 Wilson Avenue, Delta, British Columbia, Canada V4G 1E5**  
**Tel: (604) 946-3131 Fax: (604) 940-9566 Email: seisales@sei-ind.com Web site: www.sei-ind.com**

# Specifications

Fireflex Tank Capacities		1000 Imp 1200 US 4550 L	1500 Imp. 1800 US 6800 L	2000 Imp. 2400 US 9100 L	2500 Imp. 3000 US 11340 L	3000 Imp. 3600 US 13600 L	4000 Imp. 4800 US 18200 L
Part No.		1012 LP	1518 LP	2024 LP	2530 LP	3036 LP	4048 LP
Collapsed Dimension	Inches	15x24x40	15x24x44	16x30x50	18x29x48	20x29x48	26x32x48
	cm	38x60x100	38x60x111	41x76x127	46x74x122	51x74x122	66x81x122
Weight	Pounds	68	75	85	100	115	150
	kg	31	34	38	45	52	68
Filled Outside Diameter	Inches	128	154	180	188	189	224
	Metres	3.23	3.9	4.6	4.8	4.8	5.69
Collar Inside Diameter	Inches	82	102	128	132	144	164
	Metres	2.1	2.6	3.25	3.35	3.65	4.16
Height (Filled)	Inches	34	36	34	38	38	42
	Metres	0.86	0.91	0.86	0.96	0.96	1.07
Outlets	#	2	2	2	2	2	2
Size	Inches	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT	3" NPT



**The lightweight Low-Profile tank is compact and highly transportable**